

HIGH PERFORMANCE SINGLE HUNG

Designed for the weather conditions of coastal areas, High Pointe windows and doors meet stringent testing, including a DP50 structural rating.

Beveled 2 7/8" Fusion Welded PVC Frame provides lasting maintenance-free beauty.

Full Interlock & Weatherstripping at the meeting rail keeps out drafts.

3/4" Double Strength Glass and Intercept Warm Edge Spacer ensures energy efficiency.

Integral Extruded Lift Rail for confidence in operation.

Steel Reinforced Sash Rails add extra stability and structure.

Included Half Screen keeps insects out but lets the breeze in.

Recessed Tilt Latches and Double Locks* secure closure and clean appearance.

Constant Force Balance System smooth "fingertip" operation never needs adjustment.

Sloped Sill optimal water management

Fusion Welded Tilt-In / Lift Out Sash for simple, trouble-free cleaning

Limited Lifetime Warranty



PERFORMANCE DATA

NFRC Thermal Values (with IntelliGlass)

R-Value - 3.33*
Solar Heat Gain Coefficient - .31
Visible Light Transmittance- .56

Structural Values

Structural Load - 75.0 or 170 mph wind
Water Resistance - 7.5 psf
Air Infiltration - .18 cfm/ft2
AAMA Rating - R50



Structural testing standards set by AAMA.



Thermal testing standards set by NFRC.



All Vinylmax windows with optional IntelliGlass meet ENERGY STAR requirements for all regions of the USA.

