

THE  
**EDISON**  
SERIES

# VINYL REPLACEMENT WINDOWS



4600  
Double Hung

## PRODUCT FEATURES

- 3 1/4" Frame with beveled exterior
- Maintenance-free multi-chambered fusion welded vinyl
- IdeaSeal™ triple protection - integral interlock, sill compression seal and weatherstripping
- Dual function partitioned sloped sill
- Chisel bevel interior sash profiles
- Double weatherstripping on sashes
- Integral lift rails
- BioMaxx lead-free composite locks and keepers
- Flush mount tilt latches
- Double vent latches
- Concealed sash stop system
- Stainless steel constant force balances
- Metal drop in pivot cam
- Full balance covers
- Aluminum screen frame
- BetterVue screen mesh
- Intelliglass high performance glass
- Dual (3/4") or triple (1-1/8") pane glass
- Tape glazed
- Intercept Spacer System
- Limited Lifetime Warranty

## OPTIONAL FEATURES

- Sentry System hardware including dual-action tilt/lock & forced entry resistant night locks
- WOCD field applied "angel locks"
- 1-5/8" integral nailfin with 1" setback
- Super Spacer flexible warm-edge spacer system
- Tempered and STC rated glass
- Foam filled frame
- Heavy duty, full or FlexScreen
- Woodgrain interior laminates
- Black or bronze exterior laminates on white
- Interior & exterior SDL packages

## SIZE LIMITS

	Width	Height	UI*
<b>Minimum</b>	14"	24"	38
<b>Maximum</b>	52"	98"	132

MAXIMUM TRIPLE PANE SIZE 50" width x 80" height  
\*United Inches = Width + Height

**vinylmax**  
windows



2921 McBride Court  
Hamilton, OH 45011  
(800) 847-3736  
vinylmax.com

WINDOW+DOOR  
**TOP 100**  
MANUFACTURERS



**FGIA**  
Fenestration & Glazing  
Industry Alliance



4600 07-23 Information accurate at time of printing. Product subject to change. ©2023 Vinylmax LLC



THE  
**EDISON**  
SERIES

# PERFORMANCE DATA

4600 Double Hung	Intercept		Super Spacer		VLT	Energy Star	Intercept		Super Spacer		VLT	Energy Star
	U Value	SHGC	U Value	SHGC			U Value	SHGC				
IntelliGlass Low E / Argon	.28	.38	.27	.29	.53	N NC	.28	.34	.27	.26	.47	N NC
IntelliGlass X Low E / Argon	.28	.22	.27	.22	.50	NC SC S	.28	.20	.27	.20	.45	NC SC S
IntelliGlass X3 Triple Pane Low E / Argon	.24	.21	.23	.21	.46	N NC SC S	.25	.19	.23	.19	.41	N NC SC S
IntelliGlass Plus Triple Pane Low E / Argon	.20	.24	.18	.24	.40	N NC SC S	.20	.22	.18	.22	.35	N NC SC S

4650/4653 Slider	Intercept		Super Spacer		VLT	Energy Star	Intercept		Super Spacer		VLT	Energy Star
	U Value	SHGC	U Value	SHGC			U Value	SHGC				
IntelliGlass Low E / Argon	.28	.37	.27	.29	.52	N NC	.28	.34	.27	.26	.47	N NC
IntelliGlass X Low E / Argon	.28	.22	.27	.22	.50	NC SC S	.28	.20	.27	.20	.44	NC SC S
IntelliGlass X3 Triple Pane Low E / Argon	.24	.21	.23	.21	.46	N NC SC S	.24	.19	.23	.19	.41	N NC SC S
IntelliGlass Plus Triple Pane Low E / Argon	.20	.24	.18	.24	.39	N NC SC S	.20	.22	.18	.22	.35	N NC SC S

4670 Picture Window	Intercept		Super Spacer		VLT	Energy Star	Intercept		Super Spacer		VLT	Energy Star
	U Value	SHGC	U Value	SHGC			U Value	SHGC				
IntelliGlass Low E / Argon	.27	.39	.26	.30	.55	N NC	.27	.36	.26	.27	.49	N NC
IntelliGlass X Low E / Argon	.27	.23	.26	.23	.52	N NC SC S	.27	.21	.26	.21	.47	N NC SC S
IntelliGlass X3 Triple Pane Low E / Argon	.23	.22	.22	.22	.48	N NC SC S	.23	.20	.22	.20	.43	N NC SC S
IntelliGlass Plus Triple Pane Low E / Argon	.18	.25	.17	.25	.41	N NC SC S	.18	.23	.17	.23	.37	N NC SC S

Product Rating	Up to this size window*	Design Pressure PSF	Water Resistance PSF	Air Infiltration cfm/ft <sup>2</sup>
Double Hung R-PG45	40" x 63" SS glass	45	7.5	0.12
Double Hung R-PG50	40" x 63" DS glass	50	7.5	0.09
Slider R-PG25	63" x 44" SS glass	25	4.5	0.13

The lower the **U-value**, the greater a window's resistance to heat flow and the better its insulating value  
 The lower the **SHGC**, the more a product is blocking solar heat from coming through the window.  
**VLT** - Visible Light Transmittance - lower values mean less light passing through the window.

\* windows outside these size limits have not been structurally tested

