

COLORS

Solid Colors



White



Laminated Exteriors







FLEXSCREEN.

GRIDS







SCREENS





SCAN FOR MORE INFORMATION















INSPIRE COLLECTION

PRODUCT RATING: R-PG50

AIR INFILTRATION: .19 58% better than FGIA standard

SIZE LIMITS

4100 Single Hung	Width	Height	UI*
Minimum	16¹/₂"	29³/₄"	45"
Maximum	52"	98"	150"

MAXIMUM TRIPLE PANE SIZE 50" width x 80" height

AVAILABLE STYLES









2 Lite Slider (4200 Series)



PRODUCT FEATURES

- Fusion welded frame and sash corners
- Maintenance-free multi-chambered fusion welded vinyl
- 3-1/4" Frame with beveled exterior
- 1-1/2" Nail fin with 1" setback from exterior
- 3/4" Insulated glass unit
- Intercept® Spacer System
- Tilt in, lift out sash
- Full interlocking meeting rail
- Integral lift rails
- Triple weatherstripping on sashes and meeting rail
- Composite locks and horizontal fastened lock keeper
- Recessed tilt latches
- Dual function partitioned sloped sill
- Foam-filled compression bulb seal on sill
- FlexScreen® 1/2 Screen
- White or Clay vinyl

OPTIONAL FEATURES

- 3/4" J-Channel (frame option)
- Jamb Extensions (4-9/16" or 6-9/16")
- Black exterior laminate on white
- WOCD field applied "angel locks"
- Intelliglass high performance glass
- Heavy duty 1/2 (White Only)
- Full FlexScreen® (4200 Series)
- High performance reinforcement packages
- Drywall Access Option (4100 Series)



3 Lite Slider





Shapes



Patio Door

GLASS PACKAGES





IntelliGlass N



IntelliGlass INSULATION (U-VALUE)



IntelliGlass X





Triple Pane











PERFORMANCE DATA		No Grids					
		Intercept		Super Spacer			
4100 Single Hung	U Value	SHGC	U Value	SHGC	VLT	ENERGY STAR 7.0	
IntelliGlass Low E / Argon	.29	.29	.28	.29	.55		
IntelliGlass X Low E / Argon	.29	.21	.27	.21	.50	S	
IntelliGlass N Low E / Argon	.26	.47	.26	.47	.55	И	
IntelliGlass C Low E / Argon	.25	.20	.25	.20	.45	NC SC S	
IntelliGlass X3 Triple Pane Low E / Argon	.25	.20	.23	.20	.46	NC SC S	
IntelliGlass Plus Triple Pane Low E / Argon	.20	.25	.18	.25	.43	N NC	

With Grids Super Spacer

U Value	SHGC	U Value	SHGC	VLT	ENERGY STAR 7.0
.29	.26	.28	.26	.49	
.29	.19	.27	.19	.45	S
.26	.42	.26	.42	.49	N
.25	.18	.25	.18	.40	NC SC S
.26	.18	.24	.18	.41	SC S
.20	.22	.19	.22	.38	N NC SC S

^{*}United Inches = Width + Height