

THE **RADIANCE PLUS** SERIES -

# ONE WINDOW, ENDLESS POSSIBILITIES

## **COLORS**

SOLID VINYL COLORS




**INTERIORS** 

Cavalier Oak

LAMINATED

### GRIDS









Bronze

WINDOW+DOOR

LAMINATED

EXTERIORS





Heavy Duty 1/2 Screen (White Only)



**SCAN FOR MORE INFORMATION** 



ENERGY STAR MANUFACTURERS RADIANCE PLUS 06-24 Information accurate at time of printing. Product subject to change. ©2024 Vinylmax LLC







#### PRODUCT RATING: R-PG50

(Double Strength Glass)

R-PG45 (Single Strength Glass)

#### AIR INFILTRATION: .12 150% better than FGIA standard

#### **SIZE LIMITS**


4600 Double Hung	Width	Height	UI*		
Minimum	14"	24"	38″		
Maximum	52″	98"	132″		

MAXIMUM TRIPLE PANE SIZE

50" width x 80" height

\*United Inches = Width + Height

#### **AVAILABLE STYLES**



2 Lite Slider 3 Lite Slider


#### **PRODUCT FEATURES**

- 3-1/4" Frame with beveled exterior
- Maintenance-free multi-chambered fusion welded vinyl
- IdeaSeal<sup>™</sup> triple protection integral interlock, sill compression seal and weatherstripping
- Dual function partitioned sloped sill
- Cove molded interior sash profiles
- Triple weatherstripping on sashes
- Integral lift rails
- BioMaxx lead-free composite locks and keepers
- Flush mount tilt latches
- Night latches restrict sash movement for safety and security
- Concealed sash stop system
- Stainless steel constant force balances
- Metal cam balance shoe
- Full balance covers
- Dual (3/4") or triple (1-1/8") pane glass
- Tape glazed
- Intercept® Spacer System
- Limited Lifetime Warranty

#### **OPTIONAL FEATURES**

- Intelliglass high performance IGU
- 1-5/8" integral nail fin with 1" setback
- Jamb Extensions (4-9/16" or 6-9/16")
- Heavy duty or full FlexScreen®
- Black or bronze exterior laminates on white
- Woodgrain interior laminates
- Tempered and STC rated glass
- Super Spacer® flexible warm-edge spacer system
- Foam filled frame
- Sentry System dual-action tilt/lock hardware
- Interior & exterior SDL packages

## **GLASS PACKAGES**



PERFORMANCE DATA	No Grids Intercept Super Spacer				With Grids Intercept Super Spacer							
4600 Double Hung	U Value	SHGC	U Value	SHGC	VLT	ENERGY STAR 7.0	U Value	SHGC	U Value	SHGC	VLT	ENERGY STAR 7.0
IntelliGlass Low E / Argon	.29	.29	.28	.29	.54		.29	.26	.28	.26	.48	
IntelliGlass X Low E / Argon	.28	.21	.27	.21	.49	SC S	.28	.19	.27	.19	.44	SC S
IntelliGlass N Low E / Argon	.25	.46	.24	.46	.54	Ν	.25	.42	.24	.42	.49	Ν
IntelliGlass C Low E / Argon	.24	.20	.23	.20	.45	NC SC S	.24	.18	.23	.18	.40	NC SC S
IntelliGlass X3 Triple Pane Low E / Argon	.25	.20	.23	.20	.45	NC SC S	.25	.18	.24	.18	.40	NC SC S
IntelliGlass Plus Triple Pane Low E / Argon	.20	.24	.18	.24	.42	N NC	.20	.22	.19	.22	.37	N NC SC S

RADIANCE PLUS 06-24 Information accurate at time of printing. Product subject to change. ©2024 Vinylmax LLC