


RADIANCE PLUS SERIES ———

ONE WINDOW, ENDLESS POSSIBILITIES

COLORS





SCAN FOR MORE INFORMATION





SHARK TANK











RADIANCE PLUS

SERIES

PRODUCT RATING: R-PG50

(Double Strength Glass)

R-PG45 (Single Strength Glass)

AIR INFILTRATION: .12 150% better than FGIA standard

SIZE LIMITS


4600 Double Hung	Width	Height	UI*		
Minimum	14"	24"	38"		
Maximum	52"	98"	132"		

MAXIMUM TRIPLE PANE SIZE

50" width x 80" height

*United Inches = Width + Height

AVAILABLE STYLES



3 Lite Slider

Product Features

- 3-1/4" Frame with Beveled Exterior
- Multi-Chambered Fusion Welded Vinyl
- IdeaSeal[™] Triple Protection Integral Interlock, Sill Compression Seal and Weatherstripping
- Dual Function Partitioned Sloped Sill
- Cove Molded Interior Sash Profiles
- Triple Weatherstripping on Sashes
- Integral Lift Rails
- BioMaxx Lead-Free Composite Locks and Keepers
- Ergonomic Tilt Latches
- Night Latches Restrict Sash Movement for Safety and Security
- Concealed Sash Stop System
- Stainless Steel Constant Force Balances
- Metal Cam Balance Shoe
- Full Balance Covers
- Dual (3/4") or Triple (1-1/8") Pane Glass
- Tape Glazed
- Intercept® Spacer System
- Limited Lifetime Warranty

Optional Features

- IntelliGlass High Performance IGU
- 1-1/2" Integral Nail Fin with 1" Setback
- Jamb Extensions (4-9/16" or 6-9/16")
- Aluminum 1/2 Screen (White Only)
- Black or Bronze Exterior Laminates on White
- Woodgrain Interior Laminates
- 11 Painted Exterior Color Options
- Tempered and STC Rated Glass
- rTPS Spacer System
- Foam Filled Frame
- Sentry System Dual-Action Tilt/Lock Hardware
- Interior and Exterior SDL Packages

GLASS PACKAGES

Dual Pane



Triple Pane Glass is up to 50% more energy efficient than dual pane. Installing triple pane windows also reduces noise from the outside and fading from the sun.

Triple Pane















PERFORMANCE DATA No Grids					With Grids								
I ERI ORIVIAIVEE DAI	VIAINCE DAIA ,TPS		PS	Intercept				rTPS		Intercept			
4600 Double Hung		U Value	ENERGY STAR 7.0	U Value	ENERGY STAR 7.0	SHGC	VLT	U Value	ENERGY STAR 7.0	U Value	ENERGY STAR 7.0	SHGC	VLT
IntelliGlass Low E / Argon	SS	.28		.29		.29	.54	.28		.29		.26	.48
	DS	.28		.29		.28	.53	.28		.29		.26	.47
IntelliGlass X Low E / Argon	SS	.28	SC S	.28	SC S	.21	.50	.28	SC S	.28	SC S	.19	.44
	DS	.27	SC S	.28	SC S	.21	.49	.27	SC S	.28	SC S	.19	.44
IntelliGlass N Low E / Argon	SS	.25	N	.25	N	.48	.57	.25	N	.25	N	.43	.51
	DS	.24	N	.25	N	.46	.54	.24	N	.25	N	.42	.49
IntelliGlass C Low E / Argon	SS	.24	NC SC S	.24	NC SC S	.20	.46	.24	NC SC S	.24	NC SC S	.18	.41
	DS	.23	NC SC S	.24	NC SC S	.20	.45	.23	NC SC S	.24	NC SC S	.18	.40
IntelliGlass X3 Triple Pane Low E / Argon	SS	.23	NC SC S	.24	NC SC S	.20	.46	.23	NC SC S	.25	NC SC S	.18	.41
	DS	.24	NC SC S	.25	NC SC S	.20	.45	.24	NC SC S	.25	NC SC S	.18	.40
IntelliGlass Plus Triple Pane Low E / Argon	SS	.19	N NC	.20	N NC	.24	.42	.19	N NC SC S	.20	N NC SC S	.22	.37
	DS	.20	N NC	.21	N NC	.24	.41	.20	N NC SC S	.21	N NC SC S	.22	.37